

# TOSHIBA

## Toshiba Pocket PC e330 Series

e330: Intel® PXA250 at 300MHz/3.5", 240x320 TFT/32MB(ROM)-64MB(RAM)/SD/MS Pocket PC 2002

e335: Intel® PXA250 at 300MHz/3.5", 240x320 TFT/32MB(ROM)-64MB(RAM)/SD/MS Pocket PC 2002/ArcSoft PhotoBase™

### Product Highlights

- Value-priced, the Toshiba Pocket PC e330 Series is ready to use right out of the box! Powered by the Intel® PXA250 processor with Intel XScale™ technology at 300MHz and 64MB of RAM, the pocket PC e330 Series delivers a powerful feature-set to keep you productive at all times.
- The Pocket PC e330 Series features a familiar user interface and tools from Microsoft® such as Pocket Word, Pocket Excel, Pocket Outlook and Microsoft Windows™ Media Player for Pocket PC 2002
- Packaged in an attractive, sleek design, the Pocket PC e330 Series delivers brilliant images through its 3.5" TFT display offering 64K colors and an 240 x 320 resolution
- Play audio and video files, organize and view your favorite pictures, all with the Toshiba Pocket PC e330 Series' incredible expansion capabilities
- One of the thinnest PDA devices in the industry, the Pocket PC e330 weighs a mere 5.1 ounces and easily fits into a shirt pocket for the ultimate in portability.

### System Characteristics

#### Processor

- Intel® PXA250 processor at 300MHz

#### Memory

- Main memory: 64MB SDRAM; 3.3V
- Program memory: 32MB CMOS Flash ROM

#### Display

- 3.5" TFT reflective color display; 240 x 320 (portrait) resolution (16 bit)
- Front light fluorescent lamp
- 65,536 (64K) colors; 5 step Brightness control (by Software)
- MediaQ Graphics Controller; 256KB internal video memory

#### Input Devices

- **Touch Panel:** Analog resistance sensitive system touch panel
- **Controls/Buttons:** 5-way navigation button; 4 application keys- Calendar, Contacts, Task, Menu; 3 function navigator (Toshiba Scroller) for Up, Down and Action; Reset switch; Voice record button; Power on/off button; Battery on/off switch, Stylus pen

#### Expandability

- 1 SD (Secure Digital) card slot (3.3V)

#### Ports

- Universal Serial Bus port – (Client, Host\*)
- IrDA Infrared port (115kbps)
- DC-in
- Cradle connector port (26 pins)
- Stereo headphone jack

#### Physical Description

- Dimensions (LxWxH): 4.9" x 3.1" x 0.4"
- Weight: 5.1oz (w/Stylus & battery)
- LED Indicators: One 2 color (Green, Orange) LED for Power Indication:
  1. Green: Full Charge (while power source is AC adaptor)
  2. Orange: Charging (while power source is AC adaptor)
  3. Orange Flash: Alarm
  4. Yellow (Green and Orange): Out of Temperature
  5. Off: Power on/off
- User Power on Password

#### Sound

- AC-97 Codec Chip; WM9705 Sound Chip
- 16-bit stereo; 44.1KHz Sample Rate
- Full Duplex Record and Playback
- Software Volume Control (by software)
- Built-in Microphone and Built-in Speaker
- Stereo Headphone jack

#### Power Supply

- **AC Adapter:** 5V/2A DC output; 100-240V input voltage, 50/60Hz frequency
- **Battery Pack:** Rechargeable Advanced Lithium-Ion battery; 3.7V / 1000 mAh

- Battery Saver: Stand by, Display Auto Off
- Recharge time (Main battery on/off): 4h/4h

#### Operating System

- Microsoft® Pocket PC 2002

#### Additional Software

- Pocket Word
- Pocket Excel
- Pocket Outlook®
- Pocket Internet Explorer
- Microsoft® Reader
- Microsoft® Windows® Media™ Player 8 for Pocket PC
- File Explorer
- MSN® Messenger
- Microsoft® Transcriber
- Microsoft® Active Sync® 3.5
- Microsoft® Outlook® 2000
- Adobe Acrobat® Reader® for Pocket PC
- ArcSoft PhotoBase™ (e335 only)

#### Warranty

- 1 year parts, labor and battery
- 90-day limited warranty on operating system and applications

#### Environmental Specifications

- **Temperature:** Operating: 0° to 40°C (32° to 104°F); Non-operating: -20° to 65°C (-4° to 149°F)
- **Relative Humidity:** Operating: 10% to 90% non-condensing
- **Altitude (relative to sea level):**

Operating: 10,000ft (4hrs with 0°C); Altitude change rate:

2000ft/min.

Non-operating: 40,000ft (4hrs with 0°C); Altitude change rate:

2000ft/min.

- **Thermal Shock:** -35°C to 60°C, 10 to 30 cycles
- **Vibration:** Operating: 1.0G; Non-operating: 1.5G

#### Accessories

PA1309U-1PPS	USB Power Sync Cable
PA3243U-1ETC	USB Host Cable
PA3183U-1ACA	10W AC Adapter
PA3186U-1DST	USB Cradle
PA3182U-1ETC	Stylus Pen (3-pack)
PA3172U-1BTM	Bluetooth™ SD (Secure Digital) Card
SD-M3203B3	32MB SD (Secure Digital) Card
SD-M6403B3	64MB SD (Secure Digital) Card
SD-M1283B3	128MB SD (Secure Digital) Card
PA1301U-1PCS	Leather Holster Case
PA1302U-1PMS	Screen Overlays

#### Product/Part Numbers/UPC

PD330U-00001	Pocket PC e330
PD330U-00001R	Pocket PC e335

\* requires USB Host Cable (PA3243U-1ETC)